

DC METAL FACE INDUCTIVE PROXIMITY SENSOR FERROUS ONLY SENSING

Diameter
☒ Shielded ☐ Non-shielded
Switching Distance Sn: mm
Housing Material
☒ With LED ☐ Without LED

Picture

M12	
	
2 mm	4 mm
Stainless steel	
	



CE

M12	
	
2 mm	4 mm
Stainless steel	
	



CE

Operating Voltage
Ripple
No Load Current
Max. Load Current
Leakage Current
Voltage Drop
Switching Frequency
Response Time
Switching Hysteresis
Repeat Accuracy
Protection Category
Operating Temperature
Temperature Drift
Short Circuit Protection
Overload Trip Point
Material Active Face



10-30VDC	
<10%	
<10mA	
200mA	
<0.01mA	
<1.5V	
2KHZ	1KHZ
0.1ms/0.1ms	0.2ms/0.2ms
<15%(Sr)	
<1.0%(Sr)	
IP67	
-25 °C - + 70 °C	
<10%(Sr)	
YES	
220mA	
Stainless steel	

10-30VDC	
<10%	
<10mA	
200mA	
<0.01mA	
<1.5V	
2KHZ	1KHZ
0.1ms/0.1ms	0.2ms/0.2ms
<15%(Sr)	
<1.0%(Sr)	
IP67	
-25 °C - + 70 °C	
<10%(Sr)	
YES	
220mA	
Stainless steel	

DC 3 wire 10-30V NPN N.O.
DC 3 wire 10-30V NPN N.C.
DC 3 wire 10-30V PNP N.O.
DC 3 wire 10-30V PNP N.C.
DC 4 wire 10-30V Changeover PNP (N.O. & N.C.)
DC 4 wire 10-30V Changeover NPN (N.O. & N.C.)
DC 2 wire 10-60V N.O.
DC 2 wire 10-60V N.C.
DC 3 wire 10-55V NPN N.O.
DC 3 wire 10-55V NPN N.C.
DC 3 wire 10-55V PNP N.O.
DC 3 wire 10-55V PNP N.C.
DC 3 wire 5-36V NPN N.O.
DC 3 wire 5-36V NPN N.C.
DC 3 wire 5-36V PNP N.O.
DC 3 wire 5-36V PNP N.C.
DC 4 wire 5-36V Changeover PNP (N.O & N.C.)
DC 4 wire 5-36V Changeover NPN (N.O & N.C.)

[illegible][illegible]

Dimensions (unit: mm)



Cable 2M (PVC)
Weight

4 ϕ 3x0.34	
approx.67g	approx.67g

approx.30g	approx.29g
------------	------------