

INDUCTIVE SENSOR - M8

Special mini version: long distance
Cable connection

TYPE - ART. NO.

SM-10-M8-S-L-L33-D3 - SM111008

SM-10-M8-O-L-L33-D3

SM-20-M8-S-L-L33-D3 - SM208001

DESCRIPTION

10 = PNP

20 = NPN

M8 = Ø M8x1.5 - shielded


S = normally open

O = normally closed

L = Led

D3 = Sn 3mm

DIMENSIONS AND TECHNICAL DATA



Operating distance Sn	3 mm
Flush mounting	yes
Electrical version	3 wires DC
Operating voltage Ub	10...35 Vdc
Output current Ie	max. 150mA
Voltage drop Ud	max. ≤ 3.5 V
Permitted residual ripple	max. 5%
No load current Io	tip. 10mA
Frequency of operating cycles	max. 1 KHz
Hysteresis	< 10 %
Repeat accuracy	< 1 %
Permitted ambient temperature	-10...+60°C
Temperature drift	< 10 %
Led display	yellow
Protective circuit	built-in
Degree of protection	(IEC 529) IP 67
Housing material	INOX 303
Active surface material	PVDF
Connection	cable 2m, PUR, 3x0.14mm ²
Maximum torque	4.5

