

ANALOG INDUCTIVE VOLTAGE OUTPUT ANALOG SENSORS

Diameter
● Shielded ○ Non-shielded
Switching Distance Sn: mm
Housing Material
● With LED ○ Without LED

Picture

Supply Voltage
Max. Ripple
No Load Current
Output Voltage/Load Resistor
Output Current/Load Resistor
Linearity
Repeat Accuracy
Ambient Temperature
Temperature Drift
Short Circuit Protection
Reverse Polarity Protection
Protection Degree
Output Signal
Switch Frequency Max.
Time Delay Before Availability
EMC
Shock / Vibration
Material Active Face

Characteristics

Inductive Voltage Output
Inductive Current Output
Inductive Voltage & Current output


Dimensions (Unit: mm)

Cable 2M (PVC)
Weight


M 12
○
0.1-4 mm
Nickel plated brass
○


CE

18-30VDC
<10%
<35mA
0-10VDC / $\geq 2K\Omega$
-
<5%(Sr)
0.02mm
-25°C ~ +70°C
5%(Sr)
-
YES
IP67
PNP-ANALOG
100Hz
-
RFI>3V/m / EFT>1KV / ESD>4KV (contact)
IEC 60947-5-2,Part 7.4.1 / IEC 60947-5-2,Part 7.4.2
PBT



P5C2B1204GV3A2	20	P5C2B1204GVEA4	39




4 ϕ 3x0.15	—
approx.67g	approx.30g


M 18
●
1-4 mm
Nickel plated brass
○


CE

18-30VDC
<10%
15mA
0-10VDC / $\geq 4.7K\Omega$
-
<10%(Sr)
0.02mm
-25°C ~ +70°C
5%(Sr)
-
YES
IP67
PNP-ANALOG
100Hz
-
RFI>3V/m / EFT>1KV / ESD>4KV (contact)
IEC 60947-5-2,Part 7.4.1 / IEC 60947-5-2,Part 7.4.2
PBT



P5C1B1804GV3A2	20	P5C1B1804GVEA4	39




5.8 ϕ 3x0.15	—
approx.142g	approx.69g

ANALOG INDUCTIVE VOLTAGE OUTPUT ANALOG SENSORS


M18
○
1-7 mm
Nickel plated brass
○



18-30VDC
<10%
15mA
0-10VDC / $\geq 4.7K\Omega$
-
<10%(Sr)
0.02mm
-25°C ~ +70°C
5%(Sr)
-
YES
IP67
PNP-ANALOG
100Hz
-
RFI>3V/m / EFT>1KV / ESD>4KV (contact)
IEC 60947-5-2, Part 7.4.1 / IEC 60947-5-2, Part 7.4.2
PBT



P5C2B1807GV3A2	20	P5C2B1807GVEA4	39
----------------	----	----------------	----




5.8 ϕ 3x0.15	—
approx.142g	approx.69g


M30
●
5-10 mm
Nickel plated brass
○



18-30VDC
<10%
15mA
0-10VDC / $\geq 4.7K\Omega$
-
<10%(Sr)
0.02mm
-25°C ~ +70°C
5%(Sr)
-
YES
IP67
PNP-ANALOG
100Hz
-
RFI>3V/m / EFT>1KV / ESD>4KV (contact)
IEC 60947-5-2, Part 7.4.1 / IEC 60947-5-2, Part 7.4.2
PBT



P5C1B3010GV3A2	20	P5C1B3010GVEA4	39
----------------	----	----------------	----




5.8 ϕ 3x0.5	—
approx.252g	approx.187g


M30
○
7-14 mm
Nickel plated brass
○



18-30VDC
<10%
15mA
0-10VDC / $\geq 4.7K\Omega$
-
<10%(Sr)
0.02mm
-25°C ~ +70°C
5%(Sr)
-
YES
IP67
PNP-ANALOG
100Hz
-
RFI>3V/m / EFT>1KV / ESD>4KV (contact)
IEC 60947-5-2, Part 7.4.1 / IEC 60947-5-2, Part 7.4.2
PBT



P5C2B3014GV3A2	20	P5C2B3014GVEA4	39
----------------	----	----------------	----



5.8 ϕ 3x0.5	—
approx.252g	approx.187g